PROBLEM 1.22

KNOWN: Hot vertical plate suspended in cool, still air. Change in plate temperature with time at the instant when the plate temperature is 225°C.

FIND: Convection heat transfer coefficient for this condition.

SCHEMATIC:



ASSUMPTIONS: (1) Plate is isothermal, (2) Negligible radiation exchange with surroundings, (3) Negligible heat lost through suspension wires.

ANALYSIS: As shown in the cooling curve above, the plate temperature decreases with time. The condition of interest is for time t_0 . For a control surface about the plate, the conservation of energy requirement is



$$\dot{E}_{in} - \dot{E}_{out} = \dot{E}_{st} -2hA_s (T_s - T_\infty) = Mc_p \frac{dT}{dt}$$

where As is the surface area of one side of the plate. Solving for h, find

$$h = \frac{Mc_{p}}{2A_{s}(T_{s} - T_{\infty})} \left(\frac{-dT}{dt}\right)$$

$$h = \frac{3.75 \text{ kg} \times 2770 \text{ J/kg} \cdot \text{K}}{2 \times (0.3 \times 0.3) \text{m}^{2} (225 - 25) \text{K}} \times 0.022 \text{ K/s} = 6.3 \text{ W/m}^{2} \cdot \text{K}$$

COMMENTS: (1) Assuming the plate is very highly polished with emissivity of 0.08, determine whether radiation exchange with the surroundings at 25°C is negligible compared to convection.

(2) We will later consider the criterion for determining whether the isothermal plate assumption is reasonable. If the thermal conductivity of the present plate were high (such as aluminum or copper), the criterion would be satisfied.

Excerpts from this work may be reproduced by instructors for distribution on a not-for-profit basis for testing or instructional purposes only to students enrolled in courses for which the textbook has been adopted. Any other reproduction or translation of this work beyond that permitted by Sections 107 or 108 of the 1976 United States Copyright Act without the permission of the copyright owner is unlawful.